


# General Purpose Transistors

## NPN Silicon


- Moisture Sensitivity Level: 1
- ESD Rating – Human Body Model: >4000 V
  - Machine Model: >400 V

### MAXIMUM RATINGS


Rating	Symbol	Value	Unit
Collector-Emitter Voltage BC846 BC847, BC850 BC848, BC849	V <sub>CEO</sub>	65	Vdc
		45	
		30	
Collector-Base Voltage BC846 BC847, BC850 BC848, BC849	V <sub>CBO</sub>	80	Vdc
		50	
		30	
Emitter-Base Voltage BC846 BC847, BC850 BC848, BC849	V <sub>EBO</sub>	6.0	Vdc
		6.0	
		5.0	
Collector Current – Continuous	I <sub>C</sub>	100	mAdc



SOT-23



### MARKING DIAGRAM



xx= Device Marking  
(See Table Below)

### THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation FR-5 Board (Note 1.) $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	P <sub>D</sub>	225 1.8	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient (Note 1.)	R <sub>θJA</sub>	556	$^\circ\text{C}/\text{W}$
Total Device Dissipation Alumina Substrate (Note 2.) $T_A = 25^\circ\text{C}$ Derate above $25^\circ\text{C}$	P <sub>D</sub>	300 2.4	mW mW/ $^\circ\text{C}$
Thermal Resistance, Junction to Ambient (Note 2.)	R <sub>θJA</sub>	417	$^\circ\text{C}/\text{W}$
Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-55 to +150	$^\circ\text{C}$

1. FR-5 = 1.0 x 0.75 x 0.062 in

2. Alumina = 0.4 x 0.3 x 0.024 in. 99.5% alumina.



## **BC846S ~ BC850S**

## **DEVICE MARKING AND ORDERING INFORMATION**



# BC846S ~ BC850S

ELECTRICAL CHARACTERISTICS ( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Characteristic	Symbol	Min	Typ	Max	Unit
<b>OFF CHARACTERISTICS</b>					
Collector-Emitter Breakdown Voltage ( $I_C = 10 \text{ mA}$ )	$V_{(\text{BR})\text{CEO}}$	65 45 30	— — —	— — —	V
Collector-Emitter Breakdown Voltage ( $I_C = 10 \mu\text{A}$ , $V_{\text{EB}} = 0$ )	$V_{(\text{BR})\text{CES}}$	80 50 30	— — —	— — —	V
Collector-Base Breakdown Voltage ( $I_C = 10 \mu\text{A}$ )	$V_{(\text{BR})\text{CBO}}$	80 50 30	— — —	— — —	V
Emitter-Base Breakdown Voltage ( $I_E = 1.0 \mu\text{A}$ )	$V_{(\text{BR})\text{EBO}}$	6.0 6.0 5.0	— — —	— — —	V
Collector Cutoff Current ( $V_{\text{CB}} = 30 \text{ V}$ ) ( $V_{\text{CB}} = 30 \text{ V}$ , $T_A = 150^\circ\text{C}$ )	$I_{\text{CBO}}$	— —	— —	15 5.0	nA $\mu\text{A}$


## ON CHARACTERISTICS

DC Current Gain ( $I_C = 10 \mu\text{A}$ , $V_{\text{CE}} = 5.0 \text{ V}$ )  ( $I_C = 2.0 \text{ mA}$ , $V_{\text{CE}} = 5.0 \text{ V}$ )	BC846A, BC847A, BC848A BC846B, BC847B, BC848B BC847C, BC848C  BC846A, BC847A, BC848A BC846B, BC847B, BC848B, BC849B, BC850B BC847C, BC848C, BC849C, BC850C	$h_{\text{FE}}$	— — —  110 200 420	90 150 270  180 290 520	— — —  220 450 800	— — —
Collector-Emitter Saturation Voltage ( $I_C = 10 \text{ mA}$ , $I_B = 0.5 \text{ mA}$ ) ( $I_C = 100 \text{ mA}$ , $I_B = 5.0 \text{ mA}$ )	$V_{\text{CE}(\text{sat})}$	— —	— —	0.25 0.6	V	
Base-Emitter Saturation Voltage ( $I_C = 10 \text{ mA}$ , $I_B = 0.5 \text{ mA}$ ) ( $I_C = 100 \text{ mA}$ , $I_B = 5.0 \text{ mA}$ )	$V_{\text{BE}(\text{sat})}$	— —	0.7 0.9	— —	V	
Base-Emitter Voltage ( $I_C = 2.0 \text{ mA}$ , $V_{\text{CE}} = 5.0 \text{ V}$ ) ( $I_C = 10 \text{ mA}$ , $V_{\text{CE}} = 5.0 \text{ V}$ )	$V_{\text{BE}(\text{on})}$	580 —	660 —	700 770	mV	


## SMALL-SIGNAL CHARACTERISTICS

Current-Gain – Bandwidth Product ( $I_C = 10 \text{ mA}$ , $V_{\text{CE}} = 5.0 \text{ Vdc}$ , $f = 100 \text{ MHz}$ )	$f_T$	100	—	—	MHz
Output Capacitance ( $V_{\text{CB}} = 10 \text{ V}$ , $f = 1.0 \text{ MHz}$ )	$C_{\text{obo}}$	—	—	4.5	pF
Noise Figure ( $I_C = 0.2 \text{ mA}$ , $(V_{\text{CE}} = 5.0 \text{ Vdc}, R_S = 2.0 \text{ k}\Omega$ $f = 1.0 \text{ kHz}, BW = 200 \text{ Hz})$	NF	— —	— —	10 4.0	dB


## BC847, BC848, BC849, BC850




**Figure 1. Normalized DC Current Gain**




**Figure 2. “Saturation” and “On” Voltages**




**Figure 3. Collector Saturation Region**









**Figure 4. Base-Emitter Temperature Coefficient**



**Figure 5. Capacitances**




**Figure 6. Current-Gain – Bandwidth Product**


**BC846**


## SOT-23

### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.



DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.1102	0.1197	2.80	3.04
B	0.0472	0.0551	1.20	1.40
C	0.0350	0.0440	0.89	1.11
D	0.0150	0.0200	0.37	0.50
G	0.0701	0.0807	1.78	2.04
H	0.0005	0.0040	0.013	0.100
J	0.0034	0.0070	0.085	0.177
K	0.0140	0.0285	0.35	0.69
L	0.0350	0.0401	0.89	1.02
S	0.0830	0.1039	2.10	2.64
V	0.0177	0.0236	0.45	0.60

