


PNP Transistors

■ Features

- Low collector saturation voltage
- Complementary to FTC2028



■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector - Base Voltage	V_{CB0}	-100	V
Collector - Emitter Voltage	V_{CE0}	-100	
Emitter - Base Voltage	V_{EB0}	-5	
Collector Current - Continuous	I_C	-5	A
Base Current	I_B	-0.5	
Collector Power Dissipation $T_c = 25^\circ\text{C}$	P_C	30	W
Junction Temperature	T_J	150	$^\circ\text{C}$
Storage Temperature range	T_{stg}	-55 to 150	

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Collector- base breakdown voltage	V_{CB0}	$I_C = -10\text{ mA}, I_E = 0$	-100			V
Collector- emitter breakdown voltage	V_{CE0}	$I_C = -50\text{ mA}, I_B = 0$	-100			
Emitter - base breakdown voltage	V_{EB0}	$I_E = -10\text{ mA}, I_C = 0$	-5			
Collector-base cut-off current	I_{CBO}	$V_{CB} = -100\text{ V}, I_E = 0$			-0.1	μA
Emitter cut-off current	I_{EBO}	$V_{EB} = -5\text{ V}, I_C = 0$			-0.1	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = -4\text{ A}, I_B = -400\text{ mA}$			-2	V
Base - emitter saturation voltage	$V_{BE(sat)}$	$I_C = -4\text{ A}, I_B = -400\text{ mA}$			-1.2	
Base - emitter voltage	V_{BE}	$V_{CE} = -5\text{ V}, I_C = -4\text{ A}$			-1.5	
DC current gain	$h_{FE(1)}$	$V_{CE} = -5\text{ V}, I_C = -1\text{ A}$	70		240	
	$h_{FE(2)}$	$V_{CE} = -5\text{ V}, I_C = -4\text{ A}$	20			
Collector output capacitance	C_{ob}	$V_{CB} = -10\text{ V}, I_E = 0, f = 1\text{ MHz}$		270		pF
Transition frequency	f_T	$V_{CE} = -5\text{ V}, I_C = -1\text{ A}$		30		MHz

■ Classification of $h_{FE(1)}$

Type	FTA1049-O	FTA1049-Y
Range	70-140	120-240

PNP Transistors

■ Typical Characteristics

