


**PZT2222A** TRANSISTOR (NPN)

**FEATURES**

- Epitaxial planar die construction
- Complementary PNP Type available (PZT2907A)

**SOT-223**



1. BASE
2. COLLECTOR
3. EMITTER

**MAXIMUM RATINGS** (T<sub>J</sub> =25°C unless otherwise noted)

Symbol	Parameter	Value	Unit
V <sub>CBO</sub>	Collector-Base Voltage	75	V
V <sub>CEO</sub>	Collector-Emitter Voltage	40	V
V <sub>EBO</sub>	Emitter-Base Voltage	6	V
I <sub>C</sub>	Collector Current -Continuous	600	mA
P <sub>C</sub>	Collector Power Dissipation	1	W
T <sub>J</sub>	Junction Temperature	150	°C
T <sub>stg</sub>	Storage Temperature	-55~ +150	°C

**ELECTRICAL CHARACTERISTICS** (T<sub>a</sub>=25°C unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Max	Unit
Collector-base breakdown voltage	V <sub>(BR)CBO</sub>	I <sub>C</sub> = 10μ A, I <sub>E</sub> =0	75		V
Collector-emitter breakdown voltage	V <sub>(BR)CEO</sub>	I <sub>C</sub> = 10mA, I <sub>B</sub> =0	40		V
Emitter-base breakdown voltage	V <sub>(BR)EBO</sub>	I <sub>E</sub> =10μA, I <sub>C</sub> =0	6		V
Collector cut-off current	I <sub>CBO</sub>	V <sub>CB</sub> =60V, I <sub>E</sub> =0		10	nA
Collector cut-off current	I <sub>CEX</sub>	V <sub>CE</sub> =60V, V <sub>BE(off)</sub> =3V		10	nA
Emitter cut-off current	I <sub>EBO</sub>	V <sub>EB</sub> = 3V , I <sub>C</sub> =0		10	nA
DC current gain	h <sub>FE(1)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> = 0.1mA	35		
	h <sub>FE(2)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> = 1mA	50		
	h <sub>FE(3)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> = 10mA	75		
	h <sub>FE(4)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> = 150mA	100	300	
	h <sub>FE(5)</sub>	V <sub>CE</sub> =1V, I <sub>C</sub> = 150mA	50		
	h <sub>FE(6)</sub>	V <sub>CE</sub> =10V, I <sub>C</sub> = 500mA	40		
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	I <sub>C</sub> =500mA, I <sub>B</sub> = 50mA		1	V
	V <sub>CE(sat)</sub>	I <sub>C</sub> =150mA, I <sub>B</sub> = 15mA		0.3	V
Base-emitter saturation voltage	V <sub>BE(sat)</sub>	I <sub>C</sub> =500mA, I <sub>B</sub> = 50mA		2.0	V
	V <sub>BE(sat)</sub>	I <sub>C</sub> =150mA, I <sub>B</sub> =15mA		1.2	V
Transition frequency	f <sub>T</sub>	V <sub>CE</sub> =20V, I <sub>C</sub> = 20mA, f=100MHz	300		MHz
Output Capacitance	C <sub>ob</sub>	V <sub>CB</sub> =10V, I <sub>E</sub> = 0, f=1MHz		8	pF
Delay time	t <sub>d</sub>	V <sub>CC</sub> =30V, I <sub>C</sub> =150mA V <sub>BE(off)</sub> =0.5V, I <sub>B1</sub> =15mA		10	ns
Rise time	t <sub>r</sub>			25	ns
Storage time	t <sub>s</sub>	V <sub>CC</sub> =30V, I <sub>C</sub> =150mA I <sub>B1</sub> =-I <sub>B2</sub> = 15mA		225	ns
Fall time	t <sub>f</sub>			60	ns