

20V Single N-channel Trench MOSFET


FEATURES

- Fast switching
- Low RDS(ON)
- Trench MOSFET technology
- We declare that the material of product compliance with RoHS requirements and Halogen Free.



APPLICATIONS

- Low Side Load Switch
- Level Shift Circuits
- DC-DC Converter
- Portable Applications i.e. DSC, PDA, Cell Phone, etc.



DEVICE MARKING AND ORDERING INFORMATION

Device	Marking	Shipping
FTK2500NSOT883	MN	10000/Tape&Reel

MAXIMUM RATINGS($T_a = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	VDS	20	V
Gate-Source Voltage	VGS	± 6	
Drain Current(Steady State)(Note 1)	ID	1000	mA
		800	
Power Dissipation(Steady State) (Note1)	PD	950	mW
Pulsed Drain Current ($t_p = 10 \mu\text{s}$)	IDM	4	A
Operating Junction and Storage Temperature Range	TJ , Tstg	-55~+150	°C

THERMAL CHARACTERISTICS

Parameter	Symbol	Limits	Unit
Junction-to-Ambient – Steady State(Note 1)	R _{θJA}	134	°C/W

1. Surface-mounted on FR4 board using 1 in sq pad size (Cu area = 1.127 insq [1 oz] including trace







FTK2500NSOT883


ELECTRICAL CHARACTERISTICS (Ta= 25°C)

Characteristic	Symbol	Min.	Typ.	Max.	Unit
Static					
Drain-Source Breakdown Voltage (VGS =0V, ID =250µA)	V(BR)DSS	20			V
Gate Threshold Voltage (VDS =VGS , ID =250µA)	VGS(th)	0.45		0.9	V
Gate-Body Leakage Current (VDS =0V, VGS =±4.5V)	IGSS			±1.0	µA
Zero Gate Voltage Drain Current (VDS =20V, VGS =0V)	IDSS			100	nA
Drain-Source On-Resistance (VGS =4.5V, ID = 0.6A) (VGS =2.5V, ID = 0.5A) (VGS =1.8V, ID = 0.35A)	RDS(ON)		0.3 0.4 0.7	0.4 0.5 1	Ω
Diode Forward Voltage (IS =0.15A, VGS =0V)	VSD		0.7	1.2	V
Dynamic					
Total Gate Charge	(VDS =10V, VGS =4.5V, ID =0.25A)	Qg		736.3	nC
Gate-Source Charge		Qgs		93.6	
Gate-Drain Charge		Qgd		116.6	
Input Capacitance	(VDS =16V, VGS =0V, f=1MHz)	Ciss		60.67	pF
Output Capacitance		Coss		9.68	
Reverse Transfer Capacitance		Crss		5.37	
Turn-On Delay Time	(VDS = 4.5 V, RL = 47Ω, ID=200 mA, VDD = 10 V, RG = 10Ω)	td(on)		5.1	ns
Rise Time		tr		7.4	
Turn-Off Delay Time		td(off)		26.7	
Fall Time		tf		12.3	


2. Pulse test; pulse width ≤ 300 µs, duty cycle ≤ 2%.

ELECTRICAL CHARACTERISTICS CURVES



ELECTRICAL CHARACTERISTICS CURVES(Con.)


OUTLINE AND DIMENSIONS



SOT-883			
DIM	MIN	TYP	MAX
D	0.95	1.00	1.05
E	0.55	0.60	0.65
e	-	0.64	-
e1	-	0.34	-
L	0.19	0.24	0.29
L1	0.22	0.27	0.32
b	0.10	0.15	0.20
b1	0.44	0.49	0.54
A	0.43	0.48	0.53
A1	0	-	0.05

All Dimensions in mm

SOLDERING FOOTPRINT



Dimensions	(mm)
c	0.70
X	1.10
X1	0.40
X2	0.40
Y	0.20
Y1	0.55