


## 60V N-Channel MOSFETs

## General Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

## TO-252 Pin Configuration



BVDSS	RDS(ON)	ID
60V	21mΩ	38A

## Features

- 60V, 38A, RDS(ON)=21mΩ @VGS = 10V
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

## Applications

- Motor Drive
- Power Tools
- LED Lighting

Absolute Maximum Ratings ( $T_c=25^\circ\text{C}$  unless otherwise noted)

Symbol	Parameter	Rating	Units
$V_{DS}$	Drain-Source Voltage	60	V
$V_{GS}$	Gate-Source Voltage	$\pm 20$	V
$I_D$	Drain Current – Continuous ( $T_c=25^\circ\text{C}$ )	38	A
	Drain Current – Continuous ( $T_c=100^\circ\text{C}$ )	24	A
$I_{DM}$	Drain Current – Pulsed <sup>1</sup>	152	A
EAS	Single Pulse Avalanche Energy <sup>2</sup>	42	mJ
IAS	Single Pulse Avalanche Current <sup>2</sup>	29	A
$P_D$	Power Dissipation ( $T_c=25^\circ\text{C}$ )	63	W
	Power Dissipation – Derate above 25°C	0.5	W/°C
$T_{STG}$	Storage Temperature Range	-50 to 150	°C
$T_J$	Operating Junction Temperature Range	-50 to 150	°C

## Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	°C/W
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	2	°C/W



# FTK6906D

## 60V N-Channel MOSFETs

Electrical Characteristics ( $T_J=25^\circ\text{C}$ , unless otherwise noted)

### Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$ , $I_D=250\mu\text{A}$	60	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	$\text{BV}_{\text{DSS}}$ Temperature Coefficient	Reference to $25^\circ\text{C}$ , $I_D=1\text{mA}$	---	0.07	---	$\text{V}/^\circ\text{C}$
$I_{\text{DSs}}$	Drain-Source Leakage Current	$V_{\text{DS}}=60\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=25^\circ\text{C}$	---	---	1	$\mu\text{A}$
		$V_{\text{DS}}=48\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $T_J=125^\circ\text{C}$	---	---	10	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 20\text{V}$ , $V_{\text{DS}}=0\text{V}$	---	---	$\pm 100$	$\text{nA}$

### On Characteristics

$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}$ , $I_D=20\text{A}$	---	17	21	$\text{m}\Omega$
		$V_{\text{GS}}=4.5\text{V}$ , $I_D=12\text{A}$	---	20	24	$\text{m}\Omega$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$ , $I_D=250\mu\text{A}$	1.2	1.8	2.5	V
			---	5	---	$\text{mV}/^\circ\text{C}$
$g_{\text{fs}}$	Forward Transconductance	$V_{\text{DS}}=10\text{V}$ , $I_D=10\text{A}$	---	9	---	S

### Dynamic and switching Characteristics

$Q_g$	Total Gate Charge <sup>2,3</sup>	$V_{\text{DS}}=30\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $I_D=15\text{A}$	---	28	42	nC
$Q_{\text{gs}}$	Gate-Source Charge <sup>2,3</sup>		---	3.5	7	
$Q_{\text{gd}}$	Gate-Drain Charge <sup>2,3</sup>		---	6.5	10	
$T_{\text{d(on)}}$	Turn-On Delay Time <sup>2,3</sup>	$V_{\text{DD}}=30\text{V}$ , $V_{\text{GS}}=10\text{V}$ , $R_G=6\Omega$ $I_D=1\text{A}$	---	7.2	14	ns
$T_r$	Rise Time <sup>2,3</sup>		---	38	72	
$T_{\text{d(off)}}$	Turn-Off Delay Time <sup>2,3</sup>		---	34	65	
$T_f$	Fall Time <sup>2,3</sup>		---	8.2	16	
$C_{\text{iss}}$	Input Capacitance	$V_{\text{DS}}=20\text{V}$ , $V_{\text{GS}}=0\text{V}$ , $F=1\text{MHz}$	---	1680	2440	pF
$C_{\text{oss}}$	Output Capacitance		---	115	170	
$C_{\text{rss}}$	Reverse Transfer Capacitance		---	85	125	
$R_g$	Gate resistance	$V_{\text{GS}}=0\text{V}$ , $V_{\text{DS}}=0\text{V}$ , $F=1\text{MHz}$	---	2.2	4.4	$\Omega$

### Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
$I_s$	Continuous Source Current	$V_G=V_D=0\text{V}$ , Force Current	---	---	38	A
			---	---	152	A
$V_{\text{SD}}$	Diode Forward Voltage	$V_{\text{GS}}=0\text{V}$ , $I_s=1\text{A}$ , $T_J=25^\circ\text{C}$	---	---	1	V
			---	19.6	---	ns
$Q_{\text{rr}}$	Reverse Recovery Charge <sup>2</sup>	$V_{\text{GS}}=0\text{V}$ , $I_s=-1\text{A}$ , $dI/dt=100\text{A}/\mu\text{s}$	---	14.2	---	nC

Note :

1. Repetitive Rating : Pulsed width limited by maximum junction temperature.
2.  $V_{\text{DD}}=25\text{V}$ ,  $V_{\text{GS}}=10\text{V}$ ,  $L=0.1\text{mH}$ ,  $I_{\text{AS}}=29\text{A}$ ,  $R_G=25\Omega$ , Starting  $T_J=25^\circ\text{C}$ .
3. The data tested by pulsed , pulse width  $\leq 300\text{us}$ , duty cycle  $\leq 2\%$ .
4. Essentially independent of operating temperature.

## 60V N-Channel MOSFETs




Fig.1 Continuous Drain Current vs.  $T_C$




Fig.2 Normalized  $R_{DS(on)}$  vs.  $T_J$




Fig.3 Normalized  $V_{th}$  vs.  $T_J$




Fig.4  $R_{DS(on)}$  vs. Continuous Drain Current




Fig.5 Gate Charge Waveform




Fig.6 Capacitance Characteristics

## 60V N-Channel MOSFETs




Fig.7 Normalized Transient Impedance




Fig.8 Maximum Safe Operation Area




Fig.9 Switching Time Waveform





Fig.10 EAS Waveform

60V N-Channel MOSFETs

## TO-252 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	MAX	MIN	MAX	MIN
A	2.400	2.200	0.094	0.087
A1	1.110	0.910	0.044	0.036
A2	0.150	0.000	0.006	0.000
B	6.800	6.400	0.268	0.252
C	0.580	0.450	0.023	0.018
C1	0.580	0.460	0.023	0.018
D	5.500	5.100	0.217	0.201
E	2.386	2.186	0.094	0.086
F	0.940	0.600	0.037	0.024
F1	0.860	0.500	0.034	0.020
L	10.400	9.400	0.409	0.370
L1	3.000	2.400	0.118	0.094
L2	6.200	5.400	0.244	0.213
L3	1.200	0.600	0.047	0.024
θ	9°	3°	9°	3°