


150V N-Channel MOSFETs

General Description

These N-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

TO-220 Pin Configuration



BVDSS	RDSON	ID
150V	65mΩ	28A

Features

- 150V,28A, RDS(ON) 65mΩ @VGS = 10V
- VGS Guarantee $\pm 25V$
- Improved dv/dt capability
- Fast switching
- Green Device Available

Applications

- Notebook
- Load Switch
- LED applications
- Li battery pack application

Absolute Maximum Ratings (Tc=25°C unless otherwise noted)

Symbol	Parameter	Rating	Units
V _{DS}	Drain-Source Voltage	150	V
V _{GS}	Gate-Source Voltage	± 25	V
I _D	Drain Current – Continuous (Tc=25°C)	28	A
	Drain Current – Continuous (Tc=100°C)	17.7	A
I _{DM}	Drain Current – Pulsed ¹	112	A
EAS	Single Pulse Avalanche Energy ⁴	242	mJ
IAS	Single Pulse Avalanche Current ⁴	22	A
P _D	Power Dissipation (Tc=25°C)	113	W
	Power Dissipation – Derate above 25°C	0.91	W/°C
T _{STG}	Storage Temperature Range	-55 to 150	°C
T _J	Operating Junction Temperature Range	-55 to 150	°C

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
R _{θJA}	Thermal Resistance Junction to ambient	---	62	°C/W
R _{θJC}	Thermal Resistance Junction to Case	---	1.1	°C/W



FTK30N15P

150V N-Channel MOSFETs

Electrical Characteristics ($T_J=25^\circ\text{C}$, unless otherwise noted)

Off Characteristics

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_D=250\mu\text{A}$	150	---	---	V
$\Delta \text{BV}_{\text{DSS}}/\Delta T_J$	BV_{DSS} Temperature Coefficient	Reference to 25°C , $I_D=1\text{mA}$	---	0.08	---	$\text{V}/^\circ\text{C}$
I_{DS}	Drain-Source Leakage Current	$V_{\text{DS}}=150\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25^\circ\text{C}$	---	---	1	μA
		$V_{\text{DS}}=120\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=125^\circ\text{C}$	---	---	30	μA
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 25\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA

On Characteristics

$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}$, $I_D=15\text{A}$	---	52	65	$\text{m}\Omega$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_D = 250\mu\text{A}$	2	3	4	V
$\Delta V_{\text{GS(th)}}$	$V_{\text{GS(th)}}$ Temperature Coefficient		---	-2.5	---	$\text{mV}/^\circ\text{C}$

Dynamic and switching Characteristics

Q_g	Total Gate Charge ^{2,3}	$V_{\text{DS}}=75\text{V}$, $V_{\text{GS}}=10\text{V}$, $I_D=4\text{A}$	---	30	45	nC
Q_{gs}	Gate-Source Charge ^{2,3}		---	8.7	14	
Q_{gd}	Gate-Drain Charge ^{2,3}		---	8	15	
$T_{\text{d(on)}}$	Turn-On Delay Time ^{2,3}	$V_{\text{DD}}=30\text{V}$, $V_{\text{GS}}=10\text{V}$, $R_G=6\Omega$	---	14.5	28	ns
T_r	Rise Time ^{2,3}		---	19.2	18	
$T_{\text{d(off)}}$	Turn-Off Delay Time ^{2,3}		---	33.6	60	
T_f	Fall Time ^{2,3}		---	22.8	25	
C_{iss}	Input Capacitance	$V_{\text{DS}}=30\text{V}$, $V_{\text{GS}}=0\text{V}$, $F=1\text{MHz}$	---	1790	3000	pF
C_{oss}	Output Capacitance		---	160	300	
C_{rss}	Reverse Transfer Capacitance		---	82	160	
R_g	Gate Resistance	$V_{\text{GS}}=0\text{V}$, $V_{\text{DS}}=0\text{V}$, $F=1\text{MHz}$		1.4	2.8	Ω

Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_s	Continuous Source Current	$V_G=V_D=0\text{V}$, Force Current	---	---	28	A
I_{SM}	Pulsed Source Current		---	---	56	A
V_{SD}	Diode Forward Voltage	$V_{\text{GS}}=0\text{V}$, $I_s=1\text{A}$, $T_J=25^\circ\text{C}$	---	---	1.2	V
t_{rr}	Reverse Recovery Time ²	$V_{\text{GS}}=0\text{V}, I_s=1\text{A}$, $dI/dt=100\text{A}/\mu\text{s}$	---	---	---	ns
Q_{rr}	Reverse Recovery Charge ²		---	---	---	nC

Note :

- Repetitive Rating : Pulsed width limited by maximum junction temperature.
- The data tested by pulsed , pulse width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
- Essentially independent of operating temperature.
- $V_{\text{DD}}=50\text{V}$, $V_{\text{GS}}=10\text{V}$, $L=1\text{mH}$, $I_{\text{AS}}=22\text{A}$, $R_G=25\Omega$,Starting $T_J=25^\circ\text{C}$.

150V N-Channel MOSFETs




Fig.1 Continuous Drain Current vs. T_c




Fig.2 Normalized RDS(on) vs. T_j




Fig.3 Normalized V_{th} vs. T_j




Fig.4 Gate Charge Characteristics




Fig.5 Normalized Transient Impedance




Fig.6 Maximum Safe Operation Area

150V N-Channel MOSFETs




Fig.7 Switching Time Waveform





Fig.8 Gate Charge Waveform

150V N-Channel MOSFETs

TO-220 PACKAGE INFORMATION



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	9.70	10.30	0.382	0.405
A1	8.44	8.84	0.333	0.348
A2	1.05	1.25	0.042	0.049
B	15.40	16.20	0.607	0.637
C	4.28	4.68	0.169	0.184
C1	1.10	1.50	0.044	0.059
D	0.60	1.00	0.024	0.039
E	3.40	3.80	0.134	0.149
G	8.70	9.30	0.343	0.366
H	0.40	0.60	0.016	0.023
K	2.10	2.70	0.083	0.106
L	12.80	13.60	0.504	0.535
L1	2.70	3.30	0.107	0.129
M	1.10	1.50	0.044	0.059
N	2.49	2.59	0.099	0.101
T	0.345	0.355	0.014	0.014
DIA	1.45	1.55	0.058	0.061