

## General Purpose Rectifier


### ■ Features

- $I_o$  3.0A
- $V_{RRM}$  50V-1000V
- High surge current capability
- Cases: Molded plastic

### ■ Applications

- Rectifier

### ■ Outline Dimensions and Mark



### ■ Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Test Conditions	S3						
				A	B	D	G	J	K	M
Repetitive Peak Reverse Voltage	$V_{RRM}$	V		50	100	200	400	600	800	1000
Average Forward Current	$I_{F(AV)}$	A	60HZ Half-sine wave, Resistance load, $T_L=103^{\circ}C$	3.0						
Surge(Non-repetitive)Forward Current	$I_{FSM}$	A	60Hz Half-sine wave , 1 cycle , $T_a=25^{\circ}C$	100						
Junction Temperature	$T_J$	$^{\circ}C$		-55~+150						
Storage Temperature	$T_{STG}$	$^{\circ}C$		-55 ~ +150						

### ■ Electrical Characteristics ( $T_a=25^{\circ}C$ Unless otherwise specified)

Item	Symbol	Unit	Test Condition	S3						
				A	B	D	G	J	K	M
Peak Forward Voltage	$V_F$	V	$I_F=2.5A$	1.15						
Peak Reverse Current	$I_{RRM1}$	$\mu A$	$V_{RM}=V_{RRM}$	$T_a=25^{\circ}C$						
	$I_{RRM2}$			$T_a=125^{\circ}C$						
Thermal Resistance(Typical)	$R_{\theta J-A}$	$^{\circ}C/W$	Between junction and ambient				47 <sup>1)</sup>			
	$R_{\theta J-L}$		Between junction and terminal				13 <sup>1)</sup>			

#### Notes:

- 1) Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.3" x 0.3" (8.0 mm x 8.0 mm) copper pad areas

## Characteristics(Typical)

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD URGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS




FIG.4: TYPICAL REVERSE CHARACTERISTICS

