




## Bridge Rectifier

### ■ Features

- $I_o$  2.0A
- $V_{RRM}$  50V~1000V
- Glass passivated chip

### ■ Outline Dimensions and Mark



### ■ Applications

- General purpose 1 phase Bridge rectifier applications

### ■ Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions	DF2							
				005S	01S	02S	04S	06S	08S	10S	
Repetitive Peak Reverse Voltage	$V_{RRM}$	V		50	100	200	400	600	800	1000	
Average Rectified Output Current	$I_o$	A	T <sub>a</sub> =25°C 60Hz sine wave, R-load, T <sub>a</sub> =25°C	On glass-epoxy substrate							
Surge(Non-repetitive)Forward Current	$I_{FSM}$	A	60Hz sine wave, 1 cycle, T <sub>j</sub> =25°C		60						
Current Squared Time	$I^2t$	$A^2S$	1ms≤t<8.3ms T <sub>j</sub> =25°C, Rating of per diode		15						
Storage Temperature	$T_{stg}$	°C		-55 ~+150							
Junction Temperature	$T_j$	°C		-55 ~+150							

### ■ Electrical Characteristics (T<sub>a</sub>=25°C Unless otherwise specified)

Item	Symbol	Unit	Test Condition	Max
Peak Forward Voltage	$V_{FM}$	V	$I_{FM}=2.0A$ , Pulse measurement, Rating of per diode	1.1
Peak Reverse Current	$I_{RRM}$	μ A	$V_{RM}=V_{RRM}$ , Pulse measurement, Rating of per diode	10
Thermal Resistance	$R_{θ J-A}$	°C/W	Between junction and ambient, On glass-epoxy substrate	40
	$R_{θ J-L}$		Between junction and lead	15

## ■ Characteristics(Typical)




Fig. 1 - Derating Curve Output Rectified Current




Fig. 2 - Derating Curve Output Rectified Current




Fig. 3 - Typical Forward Characteristics Per Diode




Fig. 5 - Typical Junction Capacitance Per Diode




Fig. 4 - Typical Reverse Leakage Characteristics Per Diode




Fig. 6 - Typical Transient Thermal Impedance