



Schottky Barrier Rectifier Reverse Voltage 20V~40V, Forward Current 3.0 Ampere

### Features


- ◆ Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- ◆ Low power loss, high efficiency
- ◆ For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- ◆ Guardring for overvoltage protection



**DO-201AD**

### Mechanical Data

- ◆ **Case:** JEDEC DO-201AD molded plastic body
- ◆ **Terminals:** Plated axial leads, solderable per MIL-STD-750, Method 2026  
High temperature soldering guaranteed:  
250°C/10 seconds 0.375" (9.5mm) lead length,  
5lbs (2.3kg) tension
- ◆ **Polarity:** Color band denotes cathode end
- ◆ **Mounting Position:** Any
- ◆ **Weight:** 0.041 ounce, 1.15 grams



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics






( $T_A = 25^\circ\text{C}$  unless otherwise noted)

Parameter	Symbols	1N5820	1N5821	1N5822	Units
Maximum repetitive peak reverse voltage	$V_{RRM}$	20	30	40	Volts
Maximum RMS voltage	$V_{RMS}$	14	21	28	Volts
Maximum DC blocking voltage	$V_{DC}$	20	30	40	Volts
Non-repetitive peak reverse voltage	$V_{RSM}$	24	36	48	Volts
Maximum average forward rectified current 0.375" (9.5mm) lead length at $T_A=95^\circ\text{C}$	$I_{F(AV)}$	3.0			Amps
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) at $T_A=75^\circ\text{C}$	$I_{FSM}$	80.0			Amps
Maximum instantaneous forward voltage at 3.0 (Note 1)	$V_F$	0.475	0.500	0.525	Volts
Maximum instantaneous forward voltage at 9.4 (Note 1)	$V_F$	0.850	0.900	0.950	Volts
Maximum average reverse current at rated DC blocking voltage (Note 1)	$I_R$ <small>@<math>T_A = 25^\circ\text{C}</math> @<math>T_A = 100^\circ\text{C}</math></small>	2.0 20			mA
Typical thermal resistance (Note 2)	$R_{JJA}$ $R_{AJL}$	40 10			°C/W
Operating junction temperature range	$T_J$	-55 to +125			°C
Storage temperature range	$T_{STG}$	-55 to +150			°C

**Notes** 1. Pulse test: 300μs pulse width, 1% duty cycle

2. Thermal resistance from junction to lead vertical P.C.B. mounted, 0.500" (12.7mm) lead length with 2.5 x 2.5" (63.5 x 63.5mm) copper pad

## RATINGS AND CHARACTERISTIC CURVES

**Fig. 1 - Forward Current Derating Curve****Fig. 2 - Maximum Non-repetitive Peak Forward Surge Current****Fig. 3 - Typical Instantaneous Forward Characteristics****Fig. 4 - Typical Reverse Characteristics****Fig. 5 - Typical Junction Capacitance****Fig. 6 - Typical Transient Thermal Impedance**