




SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER

Reverse Voltage - 20 to 100 Volts Forward Current - 2.0 Ampere



Dimensions in millimeters

FEATURES

- ◆ The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- ◆ Metal silicon junction, majority carrier conduction
- ◆ Low power loss, high efficiency
- ◆ High forward surge current capability
- ◆ High temperature soldering guaranteed:
250°C/10 seconds, 0.375" (9.5mm) lead length,
5 lbs. (2.3kg) tension
- ◆ Green compound (halogen & Sb₂O₃ free)
- ◆ AEC-Q101 qualified

MECHANICAL DATA

Case: JEDEC SOD-123F molded plastic body

Terminals: Solderable per MIL-STD-750, Method 2026

Polarity: Color band denotes cathode end

Mounting Position: Any

Weight: 0.0007 ounce, 0.02 grams

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

	SYMBOLS	SOD220	SOD230	SOD240	SOD250	SOD260	SOD270	SOD280	SOD290	SOD2100	UNITS
	MARK	D22	D23	D24	D25	D26	D27	D28	D29	D320	
Maximum repetitive peak reverse voltage	V _{RRM}	20	30	40	50	60	70	80	90	100	VOLTS
Maximum RMS voltage	V _{RMS}	14	21	28	35	42	49	56	63	70	VOLTS
Maximum DC blocking voltage	V _{DC}	20	30	40	50	60	70	80	90	100	VOLTS
Maximum average forward rectified current	I _(AV)	2.0									Amp
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method)	I _{FSM}	40.0									Amps
Maximum instantaneous forward voltage at 2.0A	V _F	0.50			0.70		0.85				Volts
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =100°C	I _R	0.5					0.5				mA
		10.0					5.0				
Typical junction capacitance (NOTE 1)	C _J	220					80				pF
Operating junction temperature range	T _J	-65 to +125					-65 to +150				°C
Storage temperature range	T _{STG}	-65 to +150									°C


Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.



RATINGS AND CHARACTERISTIC CURVES U1A THRU U1M


AVERAGE FORWARD RECTIFIED CURRENT,
AMPERES

FIG. 1- FORWARD CURRENT DERATING CURVE




PEAK FORWARD SURGE CURRENT,
AMPERES

FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT



INSTANTANEOUS FORWARD
CURRENT, AMPERES


FIG. 3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS



INSTANTANEOUS FORWARD VOLTAGE,
VOLTS

INSTANTANEOUS REVERSE CURRENT,
MILLIAMPERES

FIG. 4-TYPICAL REVERSE CHARACTERISTICS



JUNCTION CAPACITANCE, pF

FIG. 5-TYPICAL JUNCTION CAPACITANCE

