



## Bi-Directional Triode Thyristor

Designed for high performance full-wave ac control applications where high noise immunity and high commutating di/dt are required.

## Features

- Blocking Voltage to 600 V
- On- State Current Rating of 8A RMS at 100 °C
- Uniform Gate Trigger Currents in Three Quadrants
- High Immunity to dV/dt- 1500V/us minimum at 125 °C
- Minimizes Snubber Networks for Protection
- Industry Standard TO- 220F Package
- High Commutating dI/dt- 4.0A/ms minimum at 125 °C
- Internally Isolated (2500VRMS)
- These are Pb- Free Devices



## Absolute Maximum Ratings

Symbol	Parameter			Value	Unit
I <sub>T(RMS)</sub>	RMS on-state current(full sine wave)	TO-220F	T <sub>C</sub> =100 °C	8	A
I <sub>TSM</sub>	Non repetitive surge peak on-state current(full cycle, T <sub>j</sub> initial=25 °C)	F=50Hz	t=20ms	80	A
		F=60Hz	t=16.7ms	84	
I <sup>2</sup> t	I <sup>2</sup> t Value for fusing	tp=10ms		36	A <sup>2</sup> s
D/I <sub>DT</sub>	Critical rate of rise of on-state current IG=2X <sub>IGT,tr≤100ns</sub>	F=120Hz	T <sub>j</sub> =125 °C	50	A/us
I <sub>GM</sub>	Peak gate current	tp=20us	T <sub>j</sub> =125 °C	4	A
P <sub>G(AV)</sub>	Average gate power dissipation		T <sub>j</sub> =125 °C	1	W
T <sub>stg</sub>	Storage junction temperature range			-40 to +150	°C
T <sub>j</sub>	Operating junction temperature range			-40 to +125	



# BT08F-600B

## Electrical Characteristics (T<sub>j</sub>=25°C, unless otherwise specified)

### Snubberless™ and Logic Level(3 quadrants)

Symbol	Test conditions	Quadrant	BT08F-600B		Unit
I <sub>GT</sub> (1)	V <sub>D</sub> =12V R <sub>L</sub> =30Ω	I - II - III - IV	MAX	50	mA
V <sub>GT</sub>		I - II - III - IV	MAX	1.3	V
V <sub>GD</sub>	V <sub>D</sub> =V <sub>DRM</sub> R <sub>L</sub> =3.3KΩ T <sub>j</sub> =125°C	I - II - III - IV	MIN	0.2	V
I <sub>H</sub> (2)	I <sub>T</sub> =100mA		MAX	50	mA
I <sub>L</sub>	I <sub>G</sub> =1.2I <sub>GT</sub>	I - II - III - IV	MAX	70	mA
		II		80	
D <sub>v</sub> / D <sub>t</sub> (2)	V <sub>D</sub> =67%V <sub>DRM</sub> Gate open T <sub>j</sub> =125°C		MIN	1000	V/us
(Dl/dt)c(2)	(Dv/dt) <sub>c</sub> =0.1 V/us T <sub>j</sub> =125°C		MIN	-	A/ms
	(Dv/dt) <sub>c</sub> =10V/us T <sub>j</sub> =125°C			-	
	Without snubber T <sub>j</sub> =125°C			7	

### Standard (4Quadrants)

Symbol	Test conditions	Quadrant	BT08F-600B		Unit
I <sub>GT</sub> (1)	V <sub>D</sub> =12V R <sub>L</sub> =30Ω	I - II - III IV	MAX	50 100	mA
V <sub>GT</sub>		ALL		1.3	V
V <sub>GD</sub>	V <sub>D</sub> =V <sub>DRM</sub> R <sub>L</sub> =3.3KΩ T <sub>j</sub> =125°C	ALL	MIN	0.2	V
I <sub>H</sub> (2)	I <sub>T</sub> =500mA		MAX	50	mA
I <sub>L</sub>	I <sub>G</sub> =1.2I <sub>GT</sub>	I - III - IV	MAX	50	mA
		II		100	
(Dl/dt)(2)	V <sub>D</sub> =67%V <sub>DRM</sub> Gate open T <sub>j</sub> =125°C		MIN	400	V/us
(Dl/dt)c(2)	(Dv/dt) <sub>c</sub> =3.5 A/ms T <sub>j</sub> =125°C		MIN	10	V/us

### Static Characteristics

Symbol	Test conditions			Value	Unit
V <sub>TM</sub> (2)	I <sub>TM</sub> =11A t <sub>p</sub> =380us	T <sub>j</sub> =25°C	MAX	1.55	V
V <sub>to</sub> (2)	Threshold voltage	T <sub>j</sub> =125°C	MAX	0.85	V
R <sub>d</sub> (2)	Dynamic resistance	T <sub>j</sub> =125°C	MAX	50	mΩ
I <sub>DRM</sub> I <sub>RRM</sub>	V <sub>DRM</sub> =V <sub>RRM</sub>	T <sub>j</sub> =25°C	MAX	5	uA
		T <sub>j</sub> =125°C		1	mA
V <sub>DRM</sub> /V <sub>RRM</sub>	Voltage	T <sub>j</sub> =25°C	MIN	600	V

Note 1: minimum IGT is guaranteed at 5% of IGT max


Note 2: for both polarities of A2 referenced to A1

### Thermal Resistances


Symbol	Parameter		Value	Unit
R <sub>lh(j-c)</sub>	Junction to case(AC)	TO-220F	2.5	°C/W
R <sub>th(j-a)</sub>	Junction to ambient	TO-220F	60	°C/W

## Voltage Current Characteristic of Triacs (Bidirectional Device)

Symbol	Parameter
$V_{DRM}$	Peak Repetitive Forward Off State Voltage
$I_{DRM}$	Peak Forward Blocking Current
$V_{RRM}$	Peak Repetitive Reverse Off State Voltage
$I_{RRM}$	Peak Reverse Blocking Current
$V_{TM}$	Maximum On State Voltage
$I_H$	Holding Current



Quadrant Definitions for a Triac




All polarities are referenced to MT1.


With in-phase signals (using standard AC lines) quadrants I and III are used.

## Description


**Fig. 1:** Maximum power dissipation versus RMS on-state current (full cycle).




**Fig. 2-1:** RMS on-state current versus case temperature (full cycle).




**Fig. 2-2:** RMS on-state current versus ambient temperature (printed circuit board FR4, copper thickness: 35µm), full cycle.




**Fig. 3:** Relative variation of thermal impedance versus pulse duration.



**Fig. 4:** On-state characteristics (maximum values).




**Fig. 5:** Surge peak on-state current versus number of cycles.




## Description


**Fig. 6:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 10\text{ms}$ , and corresponding value of  $I^2t$ .




**Fig. 7:** Relative variation of gate trigger current, holding current and latching current versus junction temperature (typical values).




**Fig. 8-1:** Relative variation of critical rate of decrease of main current versus  $(dV/dt)_c$  (typical values). Snubberless & Logic Level Types



**Fig. 8-2:** Relative variation of critical rate of decrease of main current versus  $(dV/dt)_c$  (typical values). Standard Types



**Fig. 9:** Relative variation of critical rate of decrease of main current versus junction temperature.



**Fig. 10:** DPAK and D<sup>2</sup>PAK Thermal resistance junction to ambient versus copper surface under tab (printed circuit board FR4, copper thickness: 35  $\mu\text{m}$ ).

