


**REVERSE VOLTGE 20V~60V,
FORWARD CURRENT 2.0AMP Schottky Barrier Rectifiers**

Features

- ◆ Metal-Semiconductor junction with guard ring
- ◆ Epitaxial construction
- ◆ Low forward voltage drop
- ◆ High current capability
- ◆ The plastic material carries UL recognition 94V-0
- ◆ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications

DO-204AC (DO-15)



Dimensions in inches and (millimeters)

Mechanical Data

- ◆ Case : JEDEC DO-204AC(DO-15) molded plastic
- ◆ Polarity : Color band denotes cathode
- ◆ Weight : 0.014 ounce, 0.39 gram
- ◆ Mounting position : Any

Maximum Ratings and Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%

Parameter	Symbols	SB220	SB230	SB240	SB250	SB260	Units
Maximum repetitive peak reverse voltage	V_{RRM}	20	30	40	50	60	Volts
Maximum RMS voltage	V_{RMS}	14	21	28	35	42	Volts
Maximum DC blocking voltage	V_{DC}	20	30	40	50	60	Volts
Maximum average forward rectified current @ $T_A=75^\circ C$	I_{AV}			2.0			Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load	I_{FSM}			60.0			Amps
Maximum forward Voltage at 2.0A DC Maximum forward Voltage at 1.5A DC	V_F		0.55	-	0.70 0.65		Volts
Maximum DC reverse current @ $T_J=25^\circ C$ at rated DC blocking voltage @ $T_J=100^\circ C$	I_R		0.5 15.0				mA
Typical thermal resistance (Note 1)	R_{QJA}		20				°C/W
Typical junction capacitance (Note 2)	C_J		150				pF
Operating junction temperature range	T_J		-55 to +125				°C
Storage temperature range	T_{STG}		-55 to +150				°C

Notes 1. Thermal Resistance Junction to Ambient.

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

RATINGS AND CHARACTERISTIC CURVES

