


**Transient Voltage Suppressors for ESD Protection General Description**

The FTV3.3BUL2 is designed to protect voltage sensitive components from ESD and transient voltage events. Excellent clamping capability, low leakage, and fast response time, make these parts ideal for ESD protection on designs where board space is at a premium. Because of its small size, it is suited for use in cellular phones, MP3 players, digital cameras and many other portable applications where board space is at a premium.



**Applications**

- Cellular phones
- Portable devices
- Digital cameras
- Power supplies

**Features**

- Small Body Outline Dimensions
- Low Body Height
- Peak Power up to 150 Watts @ 8 x 20us Pulse
- Low Leakage current
- Response Time is Typically < 1 ns
- ESD Rating of Class 3 (> 16 kV) per Human Body Model

**Ordering information**


| Device     | Marking | Shipping        |
|------------|---------|-----------------|
| FTV3.3BUL2 | B       | 10000/Tape&Reel |

**Absolute Ratings (T<sub>amb</sub>=25°C )**

| Symbol           | Parameter   | Value   | Units |
|------------------|---|---|-------|
| P <sub>PP</sub>  | Peak Pulse Power (t <sub>p</sub> = 8/20us)        | 150   | W     |
| T <sub>L</sub>   | Maximum lead temperature for soldering during 10s | 260   | °C    |
| T <sub>stg</sub> | Storage Temperature Range                         | -55 to +155                                       | °C    |
| T <sub>op</sub>  | Operating Temperature Range                       | -40 to +125                                       | °C    |
| T <sub>j</sub>   | Maximum junction temperature                      | 150   | °C    |
|                  | IEC61000-4-2 (ESD)                                | air discharge<br>± 15<br>contact discharge<br>± 8 | KV    |
|                  | IEC61000-4-4 (EFT)                                | 40  | A     |
|                  | ESD Voltage                                       | Per Human Body Model<br>16                        | KV    |

## Electrical Parameter

| Symbol    | Parameter                                   |
|-----------|---|
| $I_{PP}$  | Maximum Reverse Peak Pulse Current          |
| $V_C$     | Clamping Voltage @ $I_{PP}$                 |
| $V_{RWM}$ | Working Peak Reverse Voltage                |
| $I_R$     | Maximum Reverse Leakage Current @ $V_{RWM}$ |
| $I_T$     | Test Current                                |
| $V_{BR}$  | Breakdown Voltage @ $I_T$                   |



## Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. VF = 0.9V at IF = 10mA

| Device     | $V_{RWM}$<br>(V) | $I_R$ ( $\mu$ A)<br>@ $V_{RWM}$ | $V_{BR}$ (V) @ $I_T$<br>(Note 1) | $I_T$ | $V_C$ (V)<br>@ $I_{PP}=5$ A* | $V_C$ (V)<br>@ Max $I_{PP}$ * | $I_{PP}$<br>(A)* | $P_{PK}$<br>(W)* | C<br>(pF) |
|------------|------------------|---------------------------------|----------------------------------|-------|------------------------------|-------------------------------|------------------|------------------|-----------|
|            | Max              | Max                             | Min                              | mA    | Typ                          | Max                           | Max              | Max              | Typ       |
| FTV3.3BUL2 | 3.3              | 1                               | 3.6                              | 1.0   | 8.4                          | 14.1                          | 11.2             | 158              | 25        |

\*Surge current waveform per Figure 1.

- $V_{BR}$  is measured with a pulse test current  $I_T$  at an ambient temperature of 25°C.




Fig1. Pulse Waveform




Fig2. Power Derating Curve

SOD882 / ULP-2

DIMENSION OUTLINE

Unit:mm

